
BALL BEARING GUIDE BUSHINGS



The volume discount rate is also applicable to alteration cost.

All price & lead time are to be quoted.



Catalog No.						U/Price Q'ty : 1∼9		
Type	PD				MBB LBB			
	20	50					L	
	22	50 60					_	
MBB	25	60	80				5	
(Devcon type)	28	60	80				ě	
•	32		80	100			otati	
LBB	38		80	100			으	
(Loctite type)	45			100	120		~	
	50			100	120			
	60			100	120			
	- 50			.00	120			

PD		MBB · LBB						
Post diameter		d	Dh4		l	Α	В	
20	+0.020 +0.015	26	37	0 -0.007	4	10	6	
22		28	40					
25		31	45					
28	+0.025 +0.020	36	50		5	12	7	
32		40	55	0				
38	+0.030 +0.025 +0.035 +0.030	48	64	-0.008 0				
45		55	74		0	45	40	
50		60	83		6	15	10	
60		70	95	-0.010				

Do not cool bushing. Cooling makes residual austenite transform into martensite as in the case of sub-zero treatment, which results expansion of both outer and inner diameter of the bushing and disables to use.





Alteration	Code	Spec.	Pri	ice
		Changes full length L/2≤LC <l< td=""><td>PD20~32</td><td>ation</td></l<>	PD20~32	ation
LC L	LC	1mm increments	PD38~	Quot


■Ball bearing guide bushings —Long type—

Quantity

Rate

1~9 10~

-19



Do not cool bushing. Cooling makes residual austenite transform into martensite as in the case of sub-zero treatment, which results expansion of both outer and inner diameter of the bushing and disables to use.

d	Dh4	l	Α	В	Effective slide length	Catalog	_	LC	U/Price	Order	Catalog No LC
					ĺ1	Type	PD	1mm increments	Q'ty∶1~9	Older	1000
26	37				60		20	51~120		ركا	LBB 22 — LC100
28	40 0	4	12	7×7	00		22	61~120	□□		
31	45 -0.007				80		25	81~120	0	Delivery	5 Days
36	50	_		10×5	00		28	81~150	世		Express T
40	55	J		10/5	100	LBB	32	101~150			Express A P.i
48	64 -0.008		15	10×6	100		38	101~180	0		For area out of Singapore please refer to P.i.
55	74	c	15	10/0			45	121~180			© 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
60	83 0	6		10×8	120		50	121~200	O	■Volume discoun	
70	95 -0.010			10/8			60	121~200			0~19 20~29 30~50 5% 10% 15%

If there is only one groove machined by cutting, add a groove to make it 2.